

Temporary Strainers

Temporary Strainers are designed for temporary or short periods of operation, for example during commissioning and initial start up periods of new or reconditioned process lines to remove any coarse debris such as rags, welding rods, pipe scale, rust etc, accidentally or unavoidably present within a system.

After a nominal period of operation they are usually replaced with a permanent strainer of a finer retention.

Barton Firtop Engineering design and manufacture four types of temporary strainers; all available on competitive lead times meeting on site demands:

- Flat Disc or sometimes known as "Tennis Bat" Strainer
- "Witch Hat" Conical Basket Strainer
- "Top Hat" Conical Basket Strainer
- "Bath Tub" or "T" Type Strainer

We also undertake to make specials to suit customers requirements and also to refurbish or recycle customers existing units.

Sizes range from 3/4" (20mm) NB to 48" (1200mm) NB with pressure ratings up to 600LB as standard and specials up to 2500LB.

Flange facings include: raised, flat, serrated & ring joint, male or female.



**BARTON
FIRTOP**
ENGINEERING CO. LTD

Stoke Heath Works,
Hanbury Road, Bromsgrove,
Worcestershire B60 4LT, U.K.
Tel: (+44) 01527 831644.
Fax: (+44) 01527 832638
E-mail: sales@bartonfirtop.co.uk
www.bartonfirtop.co.uk